About Newport Water...

The original water works in Newport was started in 1876. The Newport Water Works Company was incorporated in 1881, and was succeeded by the Newport Water Corporation in 1929. Since 1936, the City of Newport has owned and operated the system. The City's legal authority to own and operate the system is stated in the City Charter and was established through RIGL_46-13-12.1. The Newport Water Division (NWD) is a division within the City of Newport's Utilities Department and is responsible for the operation and maintenance of the system. The NWD operates as an enterprise fund and is independent of the overall City budget. The NWD is regulated by the Rhode Island Public Utilities Commission.

Newport's Water Supply

Newport Water draws its raw water supply from a system of nine surface reservoirs: North Pond, South Pond, Paradise Pond, Gardiner Pond, St. Mary's Pond, Sisson Pond, Lawton Valley Reservoir, Nonquit Pond and Watson Reservoir. These reservoir systems are located in a basin area totaling 18.625 square miles or 11,920 acres of rural, forested and some developed lands. The reservoirs are interconnected through a complex network of pipelines and pumping stations. Newport Water has purchased 350 acres of conservation easements to protect raw water quality of the reservoirs.

The water is treated at either Station 1 Plant in Newport or the Lawton Valley Plant in Portsmouth. The combined capacity of the plants is 13 million gallons of treated water per day.

Newport's Distribution System

Newport Water's distribution system consists of water mains of various size, material and age which carry water throughout the City of Newport, Town of Middletown and a portion of the Town of Portsmouth to each individual customer. In addition, Newport Water provides water wholesale to the Portsmouth Water and Fire District and the U.S. Navy for distribution within their systems. Newport Water maintains within our system approximately 14,700 services, 160 miles of water main, 3,300 valves and 1,000 hydrants.

PRSRT STD
J.S. POSTAGE
PAID
NEWPORT, RI
PERMIT #286

CITY OF NEWPORT WATER DIVISION 70 Halsey Street

City of Newport

Department of Utilities
Water Division



2008 CONSUMER CONFIDENCE REPORT

Este relatório contem informação importante sobre e qualidade da agua na sua comunidade. Pergunta a quem saiba traduzir ou fala com alguem ques compreenda o que está escrito.

Este informe contiene información importante acerca de su agua potable. Haga que alguien lo traduzca para usted, o hable con alguien que lo entienda.

Newport Water Annual Water Quality Report

Newport Water is pleased to present this water quality report for 2008 to our customers. In accordance with the Safe Drinking Water Act all water utilities are required to issue an annual Consumer Confidence Report to promote customer awareness of the quality of their drinking water. This brochure is a snapshot of the water quality from January through December 2008. Included are details about where your water comes from, what it contains, and how it compares to EPA standards. In 2008, Newport Water conducted 8800 analyses to monitor approximately 80 drinking water contaminants. The following table indicates only the contaminants that were detected, even if the detected level was below the maximum level set by the EPA. For the year 2008, our system had one violation for a contaminant above the allowable level. A Public Notification was mailed to all of our customers November 2008. For more information see inside this brochure. Please be advised that the employees of Newport Water are committed to providing you the safest and most reliable drinking water possible.

If you have any questions please contact:

Julia Forgue, Dir. of Utilities (401) 845-5600

US EPA Hotline (401) 426-4791

RI Department of Health, Drinking Water Quality

(401) 222-6867

Also, information is available on the Internet:

Environmental Protection Agency www.epa.gov/safewater

Newport Department of Utilities www.cityofnewport.com/departments/ utilities/water/home.cfm

How can you be involved?

Meetings of the Newport City Council begin at 6:30 PM on the second and fourth Wednesday of each month in the Council Chambers, City Hall, 43 Broadway, Newport, RI.

Additional Health Information

To ensure that tap water is safe to drink, EPA prescribes limits on the amount of certain contaminants in water provided by public water systems. FDA regulations establish limits for contaminants in bottled water which must provide the same protection for public health.

Drinking water, including bottled water, may reasonably be expected to contain at least small amounts of some contaminants. The presence of contaminants does not necessarily indicate that water poses a health risk. More information about contaminants and potential health risk and effects can be obtained by calling the EPA's Safe Drinking Water Hotline (800) 426-4791.

The sources of drinking water (both tap water and bottled water) include rivers, lakes, streams, ponds, reservoirs, springs and wells. As water travels over the surface of the land or through the ground, it dissolves naturally-occurring minerals and radioactive material and can pick up substances resulting from the presence of animals or human activity. Contaminants that may be present in source water include:

- (A) Microbial contaminants, such as viruses and bacteria, which may come from septic systems, agricultural livestock operations and wildlife.
- (B) Inorganic contaminants, such as salts and metals, which can be naturally-occurring or result from urban storm runoff; oil and gas production, mining or farming.
- (C) Pesticides and herbicides, which may come from a variety of sources such as agriculture, storm runoff; and residential uses.
- (D) Organic chemical contaminants, including synthetic and volatile organics, which are byproducts of industrial processes and petroleum production, and can also come from gas stations, urban storm water runoff and septic systems.

(E) Radioactive contaminants, which can be naturally occurring or be the result of oil and gas production and mining activities.

Some people may be more vulnerable to contaminants in drinking water than the general population. Immunocompromised persons such as persons with cancer undergoing chemotherapy, persons who have undergone organ transplants, persons who have HIV/AIDS or other immune system disorders, some elderly, and infants can be particularly at risk of infections. These people should seek advice about drinking water from their health care providers. EPA/CDC guidelines on appropriate means to lessen the risk of infection by *Cryptosporidium* and other microbial contaminants are available from the Safe Drinking Water Hotline (800) 426-4791.

Concerning Lead in Our Water

If present, elevated levels of lead can cause serious health problems, especially for pregnant women and young children. Lead in drinking water is primarily from materials and components associated with service lines and home plumbing. The NWD is responsible for providing high quality drinking water, but cannot control the variety of materials used in plumbing components. When your water has been sitting for several hours, you can minimize the potential for lead exposure by flushing your tap for 30 seconds to 2 minutes before using water for drinking or cooking. If you are concerned about lead in your water, you may wish to have your water tested. Information on lead in drinking water, testing methods, and steps you can take to minimize exposure is available from the Safe Drinking Water Hotline or at www.epa.gov/safewater/lead.

Detected Contaminants Table

This table shows the results of our combined water-quality analyses for both Station 1 - Newport and Lawton Valley - Portsmouth systems from Jan. 1, through Dec. 31, 2008. Every regulated contaminant that we detected in the water, even in the most minute traces, is listed here along with the highest levels allowed by regulation (MCL), the ideal goals for public health, the amounts detected, the usual sources of such contamination, footnotes explaining our findings and a key to units of measurement.

| Microbiological Contaminants | <u>Period</u> | <u>Unit</u> | <u>MCL</u> | <u>MCLG</u> | <u>Detected Level</u> | <u>Range</u> | Major Sources | SDWA Violation |
|---|---------------|---------------|-------------|--------------|-----------------------|----------------|---|----------------|
| Turbidity ① | 2008 | NTU | TT | n/a | 0.83 | 99.17% | Soil runoff | No |
| Total Organic Carbon | 2008 | removal ratio | TT | n/a | 1.09 | 0.73 - 1.56 | Naturally present in environment | No |
| Rdioactive Contaminants | <u>Period</u> | <u>Unit</u> | <u>MCL</u> | <u>MCLG</u> | <u>Detected Level</u> | <u>Range</u> | <u>Major Sources</u> | SDWA Violation |
| Combined Radium * | 2008 | pCi/l | 5 | 0 | 2.00 | ND - 2.00 | Erosion of natural deposits. | No |
| Inorganic Contaminants | <u>Period</u> | <u>Unit</u> | <u>MCL</u> | <u>MCLG</u> | <u>Detected Level</u> | <u>Range</u> | <u>Major Sources</u> | SDWA Violation |
| Antimony * | 2008 | ppb | 6 | 6 | 1 | ND - 1 | Discharge from petroleum refineries; fire retardants; ceramics; electronics; solder. | No |
| Arsenic * | 2008 | ppb | 10 | 0 | 2 | ND - 2 | Erosion of natural deposits; runoff from orchards; runoff from glass and electronics production wastes. | No |
| Barium * | 2008 | ppm | 2 | 2 | 0.011 | 0.005 - 0.011 | Discharge of drilling wastes; discharge from metal refineries; erosion of natural deposits | No |
| Copper ② | 2007 | ppm | AL=1.3 | 1.3 | 0.034 | 0 | Corrosion of household plumbing systems; erosion of natural deposits; leaching from wood preservatives. | No |
| Fluoride 3 | 2008 | ppm | 4 | 4 | 1.55 | 0.09 - 1.55 | Water additive which promotes strong teeth | No |
| Lead ② | 2007 | ppb | AL=15 | 0 | 5 | 2 | Corrosion of household plumbing systems; erosion of natural deposits. | No |
| Nitrate * | 2008 | ppm | 10 | 10 | 0.5 | ND - 0.50 | Runoff from fertilizer use; leaching from septic tanks; sewage; erosion of natural deposits. | No |
| Synthetic Organic Contaminants Including Pesticides and Herbicides | <u>Period</u> | <u>Unit</u> | <u>MCL</u> | <u>MCLG</u> | <u>Detected Level</u> | <u>Range</u> | <u>Major Sources</u> | SDWA Violation |
| Benzo(a)pyrene(PAH) * | 2008 | ppt | 200 | 0 | 140 | ND - 140 | Leaching from linings of water storage tanks and distribution lines. | No |
| Di(2-ethylhexyl)phthalate * | 2008 | ppb | 4.00 | 4.00 | 4.50 | ND - 4.50 | Discharge from rubber and chemicle factories | No |
| Simazine * | 2008 | ppb | 4 | 4 | 0.25 | ND - 0.25 | Herbicide runoff | No |
| Volatile Organic Contaminants | <u>Period</u> | <u>Unit</u> | <u>MCL</u> | <u>MCLG</u> | <u>Detected Level</u> | <u>Range</u> | Major Sources | SDWA Violation |
| Total Trihalomethanes (TTHM) ④ | 2008 | ppb | 80 | n/a | 89.3 | 30.80 - 148.80 | By-product of drinking water chlorination | Yes |
| Haloacetic Acid 5 | 2008 | ppb | 60 | n/a | 29.78 | 11.50 - 80.10 | By-product of drinking water chlorination | No |
| IDSE Total Trihalmethanes ④ ⑤ | 2008 | ppb | n/a | n/a | n/a | 20.2 - 155.90 | By-product of drinking water chlorination | n/a |
| IDSE Haloacetic Acid 5 ⑤ | 2008 | ppb | n/a | n/a | n/a | 9.32 - 28.66 | By-product of drinking water chlorination | n/a |
| <u>Disinfection By-products</u> | <u>Period</u> | <u>Unit</u> | <u>MCL</u> | <u>MCLG</u> | <u>Detected Level</u> | <u>Range</u> | <u>Major Sources</u> | SDWA Violation |
| Chlorite | 2008 | ppm | 1 | 0.800 | 0.567 | <0.010 - 0.690 | By-product of drinking water disinfection | No |
| <u>Disinfectants</u> | <u>Period</u> | <u>Unit</u> | <u>MRDL</u> | <u>MRDLG</u> | <u>Detected Level</u> | <u>Range</u> | <u>Major Sources</u> | SDWA Violation |
| Chlorine | 2008 | ppm | 4 | 4 | 0.97 | 0.05 - 2.60 | Water additive used to control microbes | No |
| Chlorine Dioxide | 2008 | ppb | 800 | 800 | 750 | 30 - 750 | Water additive used to control microbes | No |
| Unregulated Contaminant Monitoring | <u>Period</u> | <u>Unit</u> | <u>MCL</u> | <u>MCLG</u> | <u>Detected Level</u> | <u>Range</u> | <u>Major Sources</u> | SDWA Violation |
| Sodium | 2008 | ppm | n/a | n/a | 34.8 | 13.20 - 34.80 | Naturally occurring; road runoff; contained in water treatment chemicals; EPA regulations require us to monitor this contaminant while EPA considers setting a limit on it. | No |

Water Quality Table Footnotes:

- ① 0.83 NTU was the highest single turbidity measurement recorded. The lowest monthly percentage of samples meeting the turbidity limit was 99.17%. Turbidity is a measure of the cloudiness of the water. We monitor it because it is a good indicator of the effectiveness of our filtration.
- ② Detected level indicates the 90th percentile value of the 30 samples taken. The Range indicates the number of samples above the action level.
- 3 Newport Water adds fluoride to its treated water as an aid in dental cavity prevention in young children.
- ① Some people who drink water containing TTHM's in excess of the MCL over many years may experience problems with their liver, kidneys or central nervous system and may have an increased risk of contracting cancer. Detected level is based on the highest four-quarter average.
- S Non-compliance data for monitoring only.
- * Sampled and monitored at raw water supply reservoirs prior to treatment.

Key to Table

AL = Action Level

MCL = Maximum Contaminant Level

MCLG = Maximum Contaminant Level Goal

MRDL = Maximum Residual Disinfectant Level

MRDLG = Maximum Residual Disinfectant Level

Goal

NTU = Nephelometric Turbidity Units

pCi/L = pico Curies per liter (a measure of radio-

activity)

ppm = parts per million, or milligrams per liter

(mg/l)

ppb = parts per billion, or micrograms per liter

(ug/l)

ppt = parts per trillion, or nanograms per liter

TT = Treatment Technique

n/a = Not applicable

Definitions

<u>Maximum Contaminant Level or MCL</u>: The highest level of a contaminant that is allowed in drinking water.

<u>Maximum Contaminant Level Goal or MCLG</u>: The level of a contaminant in drinking water below which there is no known or expected risk to health.

<u>Maximum Residual Disinfectant Level or MRDL</u>: The highest level of a disinfectant allowed in drinking water.

Maximum Residual Disinfectant Level Goal or MRDLG: The level of a drinking water disinfectant below which there is no known or expected risk to health.

Action Level (AL): The concentration of a contaminant which, if exceeded, triggers treatment or other requirement that a water system must follow.

<u>Treatment Technique (TT)</u>: A required process intended to reduce the level of a contaminant in drinking water.

The data presented in this report is from the most recent testing done in accordance with regulations. The RI Department of Health (RIDOH) allows NWD to monitor for some contaminants less than once per year because the concentrations of these contaminants do not change frequently. Some of our data, though representative, are more than one year old.

Source Water Assessments

The University of Rhode Island, in cooperation with RIDOH and other state and federal agencies, has assessed the threats to Newport Water's water supply sources. The assessment considered the intensity of development, the presence of businesses and facilities that use, store or generate potential contaminants, how easily contaminants may move through the watersheds, and the sampling history of the water. The assessment results will be used to plan source protection efforts in the future.

Our monitoring program continues to assure that the water delivered to your home is safe and wholesome. However, the assessment found that our water sources on Aquidneck Island and in Little Compton and Tiverton are moderately susceptible to contamination. This average ranking for the entire system is based on land use and existing water quality. Because most land in source water areas is privately owned, the focus of the assessments has been on identifying threats from land use so local governments, residents and water suppliers can take action to protect valuable drinking water supplies. This means monitoring and protection efforts are especially important to assure continued water quality. The complete Source Water Assessment Report is available at our office at 70 Halsey Street. The assessments are also available on the URI web site at http://www.uri.edu/ce/wg/RESOURCES/dwater/ Assessments/index.htm#summary.

About our Total Trihalomethane Violation:

The Newport Water Division routinely tests various sites within the distribution system for disinfectant byproducts (DBPs). The EPA sets standards for controlling the levels of disinfectants and DBPs in drinking water, including total trihalomethanes (TTHMs). The EPA standard for TTHMs is 80 parts per billion (ppb) for an annual running average. Compliance for TTHM is based on a running arithmetic average, computed quarterly, of quarterly averages of the eight samples that Newport analyzes. The results of tests taken indicated that at the fourth quarter of 2008, Newport Water Division's four quarter average exceeded the standard. Newport Water Division's average level of TTHMs for the four quarters of 2008 (January 1, 2008 to December 31, 2008) was 89.30 ppb.

Many water systems treat water with a chemical disinfectant, such as chlorine, in order to inactivate pathogens that cause disease. While disinfectants are effective in controlling many harmful microorganisms, they react with organic or inorganic matter in the water to form DBPs, some of which pose health risks at certain levels. Some people who drink water containing TTHMs in excess of the MCL over many years may experience problems with their liver, kidneys, or central nervous system, and may have an increased risk of getting cancer. The public health benefits of chlorine disinfection practices are significant and well recognized. Consequently, one of the most complex questions facing water supply professionals is how to reduce risks from disinfectants and DBPs while providing increased protection against microbial contaminants.

The NWD is proceeding with the engineering testing and design for a new Lawton Valley treatment plant and improvements to Station 1 treatment plant. The improvements will be procured as a Design—Build Contract. The improvements will address the regulatory requirements of the EPA's Stage 2 Disinfectants/ Disinfection Byproduct Rule, primarily the levels of Total Trihalomethanes (TTHM). The City has entered into a Consent Agreement with the RIDOH committing to have the new treatment plants in operation by December 31, 2014. For more information, visit our website at www.cityofnewport.com/departments/ utilities/water/home.cfm.